$m{47S}$ Series Notebook PC (Green ASUS)

Digital Home Hub www.asus.com

2 Spindle Merom 2.33+GHz Ready Model 17" Wide TFT **Digital Home Hub**

Specifications

Processor & Cache

n Intel Merom Duo processor, FSB=800 MHz

n Intel Merom T7100~T7700+ Processor with 4MB

On-Die L2 Cache. FSB=800MHz.

n Support Power4 Gear+ (Frequency limited + throttle)

n uFC-PGA package

n Virtualization Technology supported

n Support Power4 Gear+ (Frequency limited + throttle)

n uFC-PGA package

n AMI BIOS Code, 8Mb ISA Flash EPROM, PMU, Plug **BIOS**

n Boot from CDROM & USB FDD, Ai-Flash 4/5, LAN

n Support Intel Robinson Technology, 512MB/1GB Robinson NAND Flash optional

n PCI-Express mini card interface

n Intel® PM965 Series chipset (Crestline) 800MHz FSB + Chipset

Main Memory n 2 x SODIMM socket for expansion up to

2GB/4GB(TBD) DDRII DRAM support

n DDRII-667 MHz support

n Support dual channel

n 17" wide (16:10) active matrix TFT, WXGA+ ,1440x900 Display

(glare type / Brightness enhance version)

n Color Enhancement(Splendid) support

Graphics &

n nVidia NB8M-SE(GeForce 8400M G) w/ 128MB

VRAM support Video Module

n Support GDDR III type VRAM, 128MB

Modes

CRT Display n Depend on GeForce 8400M G

PC Cards Slot n New Card Support

n 5-in-1 MMC, SD, MS/MS-Pro, and (XD) card slot,

Support push/push type

Hard Disk Drive

n 2.5" 9.5mm SATA HDD /w Ultra DMA/100 /

S.M.A.R.T. supported

n 2.5" 12.5mm SATA 4200 RPM HDD (200 GB)

Supported capacities of 2.5"120/160/200 GB 5400RPM

(HGST) (BTO option)

n Support Ready drive.

Optical Storage n 12.7mm DVD Super-Multi drive

n Light Scribe support **Device**

Network Connectivity n Integrated PCIe(Mini Card) 802.11a/g/n (BTO option)

(a/b/g EU/RW/JP/NA, b/g CH1~11/CH1~14)

n Antenna supports 802.11a/g/n

n Intel 4965 (Kedron) supported

n Integrated Azalia compliant MDC Data/ Fax/ Voice

(Motolora M3) Modem

n On board 10/100/1000 Mbps RealTeK Fast Ethernet controller

n Full and Half duplex mode support for 10/100/1000 Mbps

n MODEM supported V.92 and universal PPT (CTR 21,

JATE, FCC, A-tick, DGT)

n Built-in Bluetooth 2.0+ EDR module (optional)

n 1.3M (Default) pixels CMOS Camera module built-in

(Factory option)

n Mini card USB interface

n Hybrid TV tuner(Analog+ DVB-T)

n Software encoding

n Terrestrial support

LED Status Indicator

Video

Camera

TV Tuner

n Power-on/Suspend

n Bat. Charging/full

n Storage device access

n Caps Lock

n Num Lock

n Power 4 Phone

n Wireless indicator

n Bluetooth indicator

n Instant launch Keys **Instant Key**

Power4 Gear +, Color Enhancement, Power 4

Phone, Touch pad lock

n Function Keys

u Fn+F1 suspend switch

Fn+F2 Wireless control

Fn+F3 E-mail

Fn+F4 Internet

u Fn+F5 Brightness down

u Fn+F6 Brightness up

u Fn+F7 LCD on/off

Fn+F8 LCD/CRT/TV-out switch display

Fn+F9 Touch Pad lock **□** Fn+F10 Volume on/mute

Fn+F11 Volume down

u Fn+F12 Volume up

Fn+Ins Numeric Key Pad on/off

Fn+Del Scroll Lock on/off

Fn+Space Power 4 Gear

Fn+CSplendid (not printed)

u Fn+↑ Stop

Play/Pause Fn+↓

Fn+ ← Previous section / Previous Track u

 $Fn+ {\:\longrightarrow\:}$ Next section / Next Track

n Slide Switch

Wireless switch for Bluetooth and WLAN

Keyboard

n 340mm keyboard with Ten-keys and MS Windows

function keys.

n 2.5mm travel

Interface

- n One Headphone-out jack / SPDIF
- n One Microphone-in jack
- n One AV-In
- n One Line-in Jack
- n One VGA port/Mini D-sub 15-pin for external DDC
- n One TV-out connector which including S-Video and Composite video signal
- n One RJ11 Modem jack
- n One RJ45 LAN Jack
- # 5*USB 2.0 ports(TBD) (1 support E-SATA)
- n One IEEE 1394 port
- n One CIR for remote control
- n One HDMI port, support HDCP
- n One External SATA port (combo with USB port)

Audio/Video

- n Built-in Azalia compliant audio chip, with 3D effect & full duplex
- n Realtek 882H
- n Dolby Digital Live Logo n Built-in 4 stereo speakers
- n Software DSP function

Power Management

- n Full feature ACPI 2.0 power management, Stand-by, Suspend to Disk, and Suspend to RAM
- n MDP 2003 compatible
- n ASUS Power4 Gear+ support

Battery Pack & Life

- n 8 cells core pack battery module, 2400mAh cell,
- n Smart battery, charging time, 4hrs/2.5hrs (System On/
- n Battery life >= 2hrs (Power Saving Mode)
- n Battery low-low enters Save-To-Disk mode

AC adapter

- n Output: 19V DC, 4.74A, 90W
- n Input: 100~240V AC, 50/60Hz universal
- n Built-in gauge IC
- n 2/3pin compact power supply system

Pointing Device

- n Built-in wide Touchpad
- n 2 click buttons with scroll area

Heat Dissipation

- n 51W thermal envelop (35W for CPU and 20W(TBD) for
- n High-exchange efficiency copper molding heatsink with heat-pipes
- n Temperature-controlled multi rotating speed cooling fan to prevent noise with "Flux Tunnel Routing"
- n Support CPU @ 65%TDP operation

Dimensions /Weight

- n 405 * 314* 38.2 mm
- n Weight 4.1kg

Security

- n BIOS setup, Power-on, HDD User Password Protection, BIOS I/O lock
- n Kensington Lock hole provided

Casing

n Plastic alloy casing A/B/C/D parts

Accessory List

USB FDD (Option)

n 1.44MB 3.5" FDD support USB v1.1

USB Accessory

- n Ai-Flash 4/ Ai-Flash5
- n Ai-Remote
- (option)
- n USB mouse (Logitech BJ79)
- n USB data transfer cable support networking and USB 2.0
- n USB-COM cable
- n USB 2.0 HDD module
- n RF Mouse

Additional Spec

S/W Utility

Asus Built or modified for Win XP:

n Asus Winflash for BIOS and Driver live Update

n Romote Controlor for MCE and Mobile Theater 4.0.

- n Power4Gear 2: Pre-defined power saving theme
- n ASUSDVD 6.0 /Cyberlink PowerDVD (w/ DVD model)
- n Asus Screen Saver
- n Asus Active Update

Shipment bundle S/W:

- n Adobe Acrobat Reader 7.0
- n Nero v6.0+ (w/ Combo model)
- n NIS 2006
- n ASUS Live Update
- n Power director
- n Mobile Theater 4.0
- n Power 4 Phone (Motorola[#M3] MDM quality issue)
 - (TBD)
- n Color Enhancement (Splendid)

Regulation

- n EMI: USA(FCC-B), TWN(BSMI), C-Tick, IDA, CCC(MIC)
- n Safety: CE, UL, CB, CCC, BSMI
- n Modem: Universal PPT including US(FCC-B), TWN(DGT), PRC (FCC68), JPN(JATE), EURO(CTR21)
- n TV Tuner Safety à CB/IEC60950-1; UL/60950-1; **BSMI**; CCC
- n TV Tuner EMI à EN55013/55020 certification
- **Support OS**

Windows Vista (Basic & Premium)

n Driver support, Vista (64-bit one Disc), Vista (32-bit One Disc)

Windows Certification

- n Compatibility: HCT V12.1A (Window XP), Win KEY
- n Language: US Int'l, JAP, TWN
- n Supported OS: Vista
- n Microsoft Direct Media Support

Keyboard Language

- n US, TWN before M/P
- n France, GR CR, DN, CZ, IT, BL, NW, PO, SF, SP, SW, SC, FR, JP, RU, UK Spain, BRA, ARB, BEL, TUR AR when M/P

request

Extra Chassis n Able to use A7 Gaming housing (G2) and EE spec (e.g. extra LCD and LED circuits).

USB Power Charger

n Left-hand side USB port support power charge when Power-off