# ThinkVision T24m-10 MONITOR

### PRODUCTIVITY AND VERSATILITY. DISPLAY OF EXCEPTIONAL VALUE.



## PROFESSIONAL PERFORMANCE WITH AFFORDABLE USB TYPE-C™.

There's no need to compromise performance and functionality for price. The affordable Lenovo<sup>™</sup> ThinkVision® T24m has it all- 23.8" of Full-HD Near-Edgeless display for outstanding images and crisp text from center to sides, along with convenient One-Cable solution USB Type-C<sup>™</sup> and broad connectivity. It is ideal for enterprise and home, office, also features full-function, ergonomic stand and TüV certification to optimize your use experience.

### WHY YOU SHOULD BUY THE LENOVO THINKVISION T24m-10 MONITOR



### Truly superior display

The brilliant 23.8" Full-HD (1920 x 1080) wide-view display features In-Plane switching for clear, vivid imagery, and response time as low as 4 ms to minimize motion blur.



#### Convenient onecable connection

A single USB Type-C<sup>™</sup> cable delivers video (DisplayPort<sup>™</sup> 1.2), data (USB 3.0) and power to a notebook, tablet or smartphone, along with versatile digital ports make device connectivity easy.

### THE LENOVO THINKVISION T24m-10 MONITOR IS BEST SUITED FOR

1

Businesses that need full, wide-screen monitors that can fit in limited deskspace.



Customer-facing environments like receptions or cash desks that need superior display performance in a compact footprint.



IT managers seeking a versatile, affordably-priced monitor suitable for mass deployment.

**Ergonomic design** 

Suits any environment with

TüV certification means

full-function adjustable stand.

reduced blue light to reduce

eye fatigue during all-day

viewing.













# Think Vision T24m-10 MONITOR

### SPECIFICATIONS

#### DISPLAY Panel Size 23.8" Temperature Panel Type In-Panel Switching 0°C - 400°C Operating Backlight -20°C - 600°C WI FD Non-Operating Resolution 1920 x 1080 Humidity Aspect Ratio 16:9 10% - 80% Operating Anti-Glare Yes Non-Operating 5% - 95% Screen Dimensions (W x H) (mm) 527.04 (H) x 296.46 (V) Altitude Maximum Brightness (Typical) 250 cd/m<sup>2</sup> 0 ft - 5000 ftOperating Viewing Angle (H/V at CR 10:1) 170°/178° Non-Operating 0 ft - 40,000 ft Contrast Ratio (Typical) 1000:1 Arsenic-Free Glass Yes Dynamic Contrast Ratio 3M:1 PVC-Free Yes 0.2745 (H) x 0.2745 (V) Pixel Pitch (mm) Mercury-Free Yes Dot/Pixel Per Inch (DP/PPI) 92 PCC % of Plastic Resins >85% 0.99 sRGB Color Gamut (CIE 1931) **Response Time** 4/6/14 ms (G-to-G) POWER CONSUMPTION DIMENSIONS (W x D x H) Size Packed Typical 17 W Maximum 110 W (mm) 638 x 188 x 420 Sleep-Mode <0.5 W (inches) 25.12" x 7.4" x 16.53" Switch Off-Mode <0.5 W Size Unpacked with Stand Power Supply Internal Lowest Position Power Voltage 90 VAC - 264 VAC 540.2 x 261.75 x 373.4 (mm)Voltage Dynamic Frequency 47 Hz - 63 Hz 21.26" x 10.3" x 14.7" (inches) **Highest Position** SIGNAL INPUT 540.2 x 261.75 x 483.4 (mm)Video Input Signals HDMI<sup>™</sup> 1.4 + DisplayPort<sup>™</sup> 1.2a + (inches) 21.26" x 10.3" x 19.03" USB Type-C<sup>+</sup> Size Unpacked without Stand Video Cables Supplied (Length) USB Type-C<sup>™</sup> to Type-C<sup>™</sup> Cable (Monitor Head Only) Video Cable Length 18 m 540.2 x 46.45 x 325.98 (mm) USB Hub Yes (inches) 21.26" x 1.83" x 12.83" USB Cable Supplied N/A Distance from Table to Panel Audio-Out Yes (3.5 mm) Lowest Pixel at Bottom of Screen SIGNAL INTERFACE / PERFORMANCE (mm / inches) 70.37 / 2.77" Highest Pixel at Top of Screen Horizontal Frequency 30 kHz - 83 kHz (mm / inches) 476.8 / 18.77" 50 Hz - 75 Hz Vertical Frequency Stand Base Footprint Area Native Resolution 1920 (H) x 1080 (V) 250 x 250 / 9.84" x 9.84" (mm / inches) Maximum Pixel Clock Speed HDMI<sup>™</sup> : 165 MHz DisplayPort<sup>™</sup> : 5.4 Gbps Weight Bandwidth USB Type-C<sup>™</sup> : 5.4 Gbps/Lane Starting at 18.52 lbs (8.4 kg) Packed 6500K Default Color Temperature Unpacked Starting at 12.34 lbs (5.6 kg) HDMI™ Preset/User Modes :19 Monitor Head Only Starting at 8.2 lbs (3.73 kg) DisplayPort™/ USB Type-C™ : 11 OSD Buttons 5 Buttons English, French, German. **OSD** Languages

### MECHANICAL

Tilt Angle (Front / Back) Swivel Angle (Left / Right) Lift (mm) Pivot VESA® Mount (mm x mm) Kensington<sup>®</sup> Lock Slot Cable Management **Bezel** Color **Bezel Width** Top (mm / inches) Bottom (mm / inches) Sides (mm / inches)

Spanish, Italian, Japanese, Simplified Chinese, Russian

COMPLIANCE EPEAT™

ENERGY STAR® Rating ULE TCO® RoHS (EU 2002/95/EC) Windows Certification China Energy Efficiency Standard Gold 7.0 Gold TCO 7.0 / TCO Edge 2.0 Yes Windows 7 / Windows 10 Tier 2

#### WARRANTY AND AVAILABILITY

Warrantv Geography Availability 3 Years ww



-5° / 30°

Yes (110)

Yes (100 x 100)

+/-45°

+/-90°

Yes



Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible for any editorial, photographic or typographic errors. All images are for Lenovo reserves the right to alter product ofterings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible tor any editorics. Trademarks: The following are trademarks or registered tademarks or ensure accuracy of all information but is not liable or responsible tor any editorics. Trademarks: The following are trademarks or registered tademarks or ensure accuracy of all information but is not liable or responsible tor any editorics. Trademarks: The following are trademarks or ensure trademarks or ensure accuracy of all information but is not liable or responsible tor any editorics. Trademarks: The following are trademarks or registered tademarks or ensure trademarks or ensure trademarks

### ENVIRONMENTAL