

UTS2

FLASH DRIVE

USB 2.0

Main features

- Functional revolving housing
- Durable material with metal shield
- Available capacities: 4, 8, 16, 32, 64, 128 GB
- Lifetime warranty



Versatility and functionality are the most important features of UTS2. The durable housing, with revolving metal shield, not only perfectly protects stored data, but also guarantees no hassle since you won't lose the cap. UTS2, as opposed to other products available in the market, is characterized by quality components and lifetime warranty.

Parameters

Available capacities	4, 8, 16, 32, 64, 128 GB
Interface	USB 2.0 Compatibility with USB 2.0 i 1.1
Max. transfer	read: up to 20 MB/s write: from 5 MB/s
Dimensions	57,1 × 19,3 × 10,7 mm
Blister dimensions	103 mm x 123 mm
Weight	15 g
Operating temperature	0 to +70°C (recommended)
Storage temperature	-25 to +85°C (recommended)
OS Compatibility	Windows 2000 SP4 and higher MacOS 10.5.x and higher Linux v.2.6.x and higher

Logistics data

Product	MOQ	P/N	EAN
4GB UTS2 BLACK USB 2.0	20	UTS2-0040K0R11	5908267920718
8GB UTS2 BLACK USB 2.0	20	UTS2-0080K0R11	5908267920404
16GB UTS2 BLACK USB 2.0	20	UTS2-0160K0R11	5908267920350
32GB UTS2 BLACK USB 2.0	20	UTS2-0320K0R11	5908267920381
64GB UTS2 BLACK USB 2.0	20	UTS2-0640K0R11	5908267920398
128GB UTS2 BLACK USB 2.0	20	UTS2-1280K0R11	5908267920312
8GB UTS2 BLUE USB 2.0	20	UTS2-0080B0R11	5908267920756
16GB UTS2 BLUE USB 2.0	20	UTS2-0080B0R11	5908267920770