

22x8x8x /22x6x8x/12x/16x/ + 48x32x48x

Features Super AllWrite iHAS122

* SATA interface, Half-Height internal DVD+R / DVD+RW / DVD-RW / DVD-R9/ DVD-R9/ DVD-RAM/ DVD-ROM / CD-R/ CD-RW / CD-ROM combination drive

- ★ Support Double Layer DVD+/- R9 Recording Function
- ★ SMART-BURN(*1) avoiding Buffer Under Run error, Automatically adjusting writing strategy & walking OPC to provide the best burning quality
- * SMART-X(*2) function adjusts CD-DA / VCD / DVD data extraction to a fastest allowable speed according to both data request rate from host and disk quality
- * ABS system reduce vibration and noise during recording and reading
- ★ Support Fixed Packet, Variable Packet, TAO, SAO, DAO, Random Access Write, Incremental, sequential recording, restricted overwrite, Layer Jump recording, Raw Mode Burning & Over-Burn
- **★** DVD read compliant: DVD single/dual layer (PTP/OTP), DVD-R(3.9GB/4.7GB), DVD-R multi-borders, DVD-RAM DVD+R, DVD+R multi-sessions, DVD-RW, and DVD+RW
- ★ CD read compliant: CD-DA, CD-ROM, CD-ROM/XA, Photo-CD, Multi-session, Karaoke-CD, Video-CD, CD-I FMV, CD Extra, CD Plus, CD-R, and CD-RW
- * Support both 8cm and 12cm disc of CD and DVD family
- ★ Conform to Orange Book: Part 2 CD-R Volume 1, Part 2 CD-R Volume 2 Multi Speed, Part 3 CD-RW Volume 1 (1x, 2x, and 4x), Part 3 CD-RW Volume2: High Speed, Part 3 CD-RW Volume 3: Ultra Speed
- * Supported transfer mode: PIO mode 4, DMA mode 2 and Ultra DMA mode 4

Specifications

DVD Family :

Write

DVD+R 22X maximum by CAV
DVD-R 22X maximum by CAV
DVD+R9 8X maximum by Zone CLV
DVD-R9 8X maximum by Zone CLV
DVD-RAM 12X maximum by PCAV

ReWrite

DVD+RW 8X by Z-CLV DVD-RW 6X by CLV

Read 16X maximum by CAV

Rand. access time 160ms

CD Family :

Write

CD-R 48X by CAV

ReWrite

CD-RW 32X maximum by Z-CLV in UltraSpeed disc

Read 48X maximum by CAV

Rand. Access Time 140ms

Buffer Size: 2MB(MAX)

PC Required : Pentium 4 1.3GHz or higher CPU and 128MB or higher RAM are required

HDD must have access time $<\!20$ ms; with a minimum of 650MB free space

9GB free space for creating a DVD image file (9GB for double layer; 5GB for single layer)

Software Required: SmartErase enabled application software

Compatibility: MS 2000/ XP/ VistaMTBF(Life): 70000 POH

Environment :

Operating 5°C to 50°C; Relative Humidity: 15% to 80% Non-Operating -40°C to 65°C; Relative Humidity: 15% to 95%

Dimension: 146(W) x 41.3(H) x 170(D) mm

Weight: <0.9 Kg</p>

Voltage Requirements :

+5V +/-5% and less than 100 mVp-p ripple voltage +12V +/-10% and less than 200 mVp-p ripple voltage

- *1 SMART-BURN: Smart Monitoring & Adapting Recording Technology for BURNing.
- *2 SMART-X: Smart Monitoring & Adjusting Read-speed Technology for eXtraction.