$\underline{W2W}$ Series Notebook PC



WWW (Wide, Wise, Wild)

2-Spindle, Santa Rosa 17"(16:10) & Intel 965PM + M76M-256M(ATI Mobility Radeon HD 2600)

| Processor & | Intel Merom T7700/T7500/T7300 Processor with IMP On Dia L2 Costs 500 Mag | On-screen- | ■ Brightness |
|-----------------|---|----------------|---|
| Cache | 4MB On-Die L2 Cache. FSB=800Mz. | Display | Display selection LCD/Ext. Monitor/Dual/TVout |
| BIOS | ■ AMI 8 Mb Flash EPROM, PMU, Plug & Play. | | LCD on/off |
| | Boot from IDE CD-ROM and USB FDD | | AC adapter plug in/ Battery in use Pad lock enable/disable |
| | Boot from USB, LAN, Ai-Flash 3, Ai-Flash 4, | | Power 4 Gear+ mode |
| | Ai-Flash 5 | | ■ DSP switch |
| Chipset | ■ Intel [®] 965PM Series (Crestline) 800MHz FSB + ICH8M | TV Tuner | Mini card interface |
| Intel Turbo | Support Intel Turbo Memory (Option) | (Factory | ■ Hybrid TV tuner(Analog+ DVB-T) |
| Memory | Mini-Card interface (1G) | option) | |
| (Option) | | Video Camera | 0.3 M pixels CMOS Camera |
| Main Memory | ■ 2 x SODIMM sockets for expansion up to 2GB (BTO | Keyboard | ■ 19 mm full size 88key with MS-Windows function |
| | option) | | keys |
| | OMB on board memory DDB2 (C7 DDAM) | | ■ 2.7mm travel |
| | DDR2 667 DRAM support Support Dual Channel | Interface | Internal Mic with eco cancellation 2 MGD 2 0 |
| Display | Support Dual Chamel 17" (16:10) active matrix TFT | | 3 USB 2.0 ports (at least one in right), one of the USB ports is the 5V Charger. |
| Display | ■ WSXGA+ glare | | One Microphone-in jack/Center, Woofer |
| | ■ WUXGA+ glare | | One Line-in Jack/ surround |
| Graphics & | ATI M76-M (ATI Mobility Radeon HD 2600) | | ■ One Headphone-out (Stereo), SPDIF combo jack/ From |
| Video Module | External 256MB VRAM (GDDRIII VRAM*4, 16*32) | | channel |
| | DX10 Support H.264/VC-1 Hardware decoding | | One Audio/ Video in Jack |
| | H.204/VC-T Hardware decoding HDCP support | | One RF connector |
| | | | One RJ11 Modem jack for phone line One RJ45 LAN Jack for LAN insert |
| CRT Display | Depends on ATI Mobility Radeon HD 2600 | | One RJ45 LAN Jack for LAN insert One 1394 A Type jack |
| Modes | VGA 640 x 480 256/64K/16.7M colors | | One CIR for remote control |
| incuco | SVGA 800 x 600 256/64K/16.7M colors | | One S-video Connector which including S-signal and |
| | XGA 1024 x 768 256/64K/16.7M colors UXGA 1600 x1200 256/64K/16.7M colors | | Composite signal & component signal |
| PC Cards Slot | New Card Type | | One VGA port/Mini D-sub 15-pin for external DDC |
| | | | monitor |
| Smart Media | One built-in 8-in-1 card reader support | | One HDMI |
| Reader | MMC/ SD/ Mini-SD /XD | 0.101/0.000 | One External SATA |
| | Memory Stick/ MS Pro/ MS-Duo/ | Switch/Button/ | Power button (1 color to show Direct Media/ Windows |
| | ♦ MS-Pro-Duo | Hot Keys | mode) TBD |
| Hard Disk Drive | ■ 2.5" 9.5mm/12.5mm IDE HDD | | Instant launch keys: 5 buttons |
| | SATA interface 4200/5400 RPM support | | ♦ Windows mode: ASUS mobile theater or MCE, |
| | Capacities of 160/200/300 GB | | Color enhancement, RF console(WLAN/ |
| Network | ■ Integrated V.92 MDC Fax/ Modem, with Azalia-Link | | Bluetooth), Pad-lock, P4 Gear+ |
| Connectivity | Compliant | | ♦ S5 mode: Instant Fun Plus |
| - | Worldwide regulation, FCC/JATE/CTR21/DGT | | ◆ AV launch keys: 7 buttons |
| | compliance | | Instant Fun Plus/ Windows mode: TV record, TV, |
| | 10/100/1000 bps LAN built-in | | |
| Wireless LAN | Integrated Intel Kedron 802.11a/b/g/n, | | DVD/CD, Channel +/-, Volume +/- (previous |
| (Factory | (Support Antenna 2x3 and 2x2) | | chapter/ STOP/ Pause & Play / next chapter) |
| option) | Golan 802.11 a/b/g, (BTO option) | | ◆ S5 mode: TV, DVD/CD |
| | Antenna supports 802.11a/g/n | | Function keys |
| | ■ Intel Kedron supported | | ♦ Fn+F1 Suspend switch |
| | ■ Build-in Bluetooth 2.0+EDR | | ◆ Fn+F2 Wireless switch(same as W2 is better, |
| Optical Device | ■ 5.25"/12.7 mm DVD Super Multi (DVD+RW & | | depend on ID design) |
| | DVD-RW) with Light-scribe | | ◆ Fn+F4 Audio DSP switch |
| | HD-DVD Tray type | | ♦ Fn+F5 Brightness down |
| | BD (Blue-Ray DVD) Tray type | | ♦ Fn+F6 Brightness up |
| LED Status | Power-on/Suspend | | ♦ Fn+F7 LCD only |
| Indicator | Bat. Charging/full/low | | |
| | Storage device (HDD) access | | Fn+F8 LCD/CRT/TV display switch |
| | Storage device (ODD) access | | ◆ Fn+F10 Mute |
| | Cap. Lock | | ♦ Fn+F11 Volume down |
| | | | ♦ Fn+F12 Volume up |
| | Num Lock E-mail in box | Audio | Azalia with 24bit 8-channel audio support |
| | 802.11 Access/Activity | | Built-in 5 stereo speakers with high/middle/low pitched separate.(include one built-in sub-woofer) |
| | | 1 | |
| | Bluetooth activity | | Dolby certification(Dolby Home Theater) |

Specifications are subject to change without notice. All brand names, trademarks or registered trademarks are the property of their respective holders.

| Management | Stand-by, Suspend to Disk, and Suspend to RAM |
|----------------|---|
| management | Support New Battery charging policy. |
| Battery Pack & | ■ Li-Ion 8 cells, 14.8V, 5200mAh, 71Wh battery pack |
| Life | Built-in gauge IC |
| LIIE | Battery life: 2Hrs (TV SKU in performance mode) |
| | Charging time, TBD |
| | Battery low warning under Windows environment |
| | Enters Save-To-Disk mode automatically when battery |
| | is less than 5% |
| AC adapter | Output: 19V DC, 4.7A, 90W |
| • | Input: 100~240V AC, 50/60Hz universal |
| Pointing | Built-in touchpad |
| Device | 2 click buttons |
| Heat | ■ 35W CPU, 7W chipset & 18W graphic thermal envelop |
| Dissipation | High-exchange efficiency copper molding heat sink |
| | with heat-pipes |
| | Temperature-Controlled cooling fan |
| | |
| Support OS | Windows Vista (64/32 bit), 64/32-bit Driver CD with |
| | Driver WHQL support. |
| Dimension | ■ 395x286x25.5~32.5mm(TBD) |
| /Weight | \blacksquare 3.3~3.4Kg(TBD) |
| Security | ■ <u>TPM 1.2</u> |
| - | Pre-OS Authentication by programmable key code |
| | BIOS Booting User Password Protection |
| | ■ HDD User Password Protection and Security Lock |
| | Kensington Lock hole provided |
| | - mensington zoen note provided |

Accessory list

| Remote Control | New card type |
|----------------|--|
| | Working with Audio/MP3/DVD & TV tuner |
| | Buttons for play/pause, Stop, Forward, Rewind |
| | Number buttons of 0, 1,9(no need for new card type) |
| | Buttons for Up/Down, Enter, Left/Right |
| | Buttons for Volume Up/Down & Channel Up/Down |
| | Support Vista |
| Headset | ASUS design wired headsets |
| Carry bag | ASUS design carry bag |

Software & Application

| Direct Media | Asus Win flash for BIOS and Driver live Update |
|--------------|--|
| | ASUS DVD 3 in 1: ASUS DVD 2000 / Cyber link |
| | Power DVD (w/ DVD model) w/ latest qualified |
| | version /Nero |
| | Asus Live Update |
| | Asus Life frame II |
| | Virtual Camera |
| | ASUS Multi-Frame |
| | ASUS Wireless Console |
| | Net 4 switch |
| | Power 4 Phone |
| | Asus NB Probe |
| | Color Enhancement (Splendid) |
| | Infineon Security Platform Host SW |
| | ■ ADSM |
| | New OSD |
| | Shipment bundle S/W: |
| | Norton Internet Security 2007 |
| | Nero V6.x (Bundle with CD/DVD recorder)ASUS |
| | Live Update V2 |
| | |
| HD & BD | ■ IVI WinDVD for ASUS. Support HD & BD version |
| application | |
| | |

Additional Spec

| Regulation | EMI: USA(FCC-B), JAP(VCCI-B), BSMI, CCC Safety: CE, CB, cUL, CCC, BSMI Modem: Universal PPT including US, TWN, PRC, JPN, EURO, (CTR 21, JATE, FCC, A-tick, DGT) Wireless RF Certification: TWN, CHN, FCC, European, Telec |
|--------------------------|--|
| Windows Certification | Compatibility: HCT V12.1 (Window XP), WinKey Language: US, JPN, TWN Supported OS: Windows Vista |
| Keyboard Language | US, UK, JPN(big enter key), ARB, BEL, BRA, CAN, CZH, DEL, DEN, DUH, FRN, GER, HEB, HUN, ITY, |
| | |

| KOR, NOW, POT, RUS, SPA, SWD, SWF, SWG, TAI, | |
|--|--|
| TUR, TWN, NORDIC (All of the K/B should be Vista | |
| Ready) | |

Specifications are subject to change without notice. All brand names, trademarks or registered trademarks are the property of their respective holders.