



A-LINK[®]

A-LINK IPC2OUT Wireless outdoor PAN/TILT IP camera

Outdoor case specification :

- Steel case
- Dimension 175 x 219mm
- Heater 15W (ON +5C°, OFF +10C°)
- Fan (ON +45C°, OFF +30C°)
- IP 66
- Wall mounting kit
- Length 90mm
- Roof mounting kit
- Length 310mm
- 12V / 1.5A DC power adapter
- Weight ~3Kg (outdoor case & camera)

Camera specification :

- Image Sensor :
 - Image sensor: 1/4 Color CMOS Sensor
 - Resolution: 640x480
 - Minimum illumination: 0.5 LUX
 - IR-led's disabled (HW)
- Lens :
 - Lens type: Board lens
 - Aperture: 1.8
 - Focus Length: 4.0mm
 - View angle(diagonal): 64°
- Image Processing :
 - Compression: MPEG4 / MJPEG
 - 3GPP support
 - Auto exposure control
 - Auto white balance
 - Auto gain control
 - Image resolution:
 - VGA (640x480)
 - QVGA (320x240)
 - QQVGA (160x120)
- System :
 - Network processor: ARM9
 - System ROM: 8Mb flash
 - System RAM: 32Mb SDRAM
 - Power: DC 12V / 1.5A
 - Operation temp: 0~45C°
 - Storage temp: -15~60C°
- Communication :
 - Ethernet: 1pcs RJ45 port 10/100Mb
 - Wireless: 802.11b/g with external antenna(SMA)
 - GPIO: 1 in / 1 out
 - USB 1.1 port for external memory
- Supported protocols:
 - TCP/IP, DHCP, FTP, HTTP, UPnP, SMTP, DNS, DDNS, ICMP, PPPoE, UDP, NTP, BONJOUR (MAC Os)
- LED and Button :
 - Power LED
 - Link/act. LED
 - Reset button: Push and hold 5 sec.
- Audio :
 - Internal Omni-directional Microphone
 - Sensitivity: -48dB +/- 3dB
 - Freq Response: 50~16000Hz
 - Active speaker: Mono
 - Audio codec PCM / AMR
- PAN-TILT :
 - Pan range +165 ~ -165 degree
 - Tilt range +90 ~ -15 degree
 - 8 preset positions

• Camera Features:

- System management: Web based, Application soft.
- User levels: Guest, General, Administrator
- Setup Wizard
- Image setting: Brightness, Sharpness, Saturation
- Support upside down and mirror
- Digital zoom: 3x
- Frame rate setting: 1-25fps / Auto
- 3GPP support
- Compression setting:
 - Lowest, Low, Normal, High, Highest
- IP setting:
 - Static, DHCP, PPPoE
- Email support:
 - SMTP mail, scheduling, two destination Emails
- Time management:
 - Manual, server and NTP
- Motion event management:
 - Motion detection (2 scalable windows), schedule or GPIO switching.
 - Image Upload/Send to PC, Network Storage, USB Flash disk, over Email or FTP.
- IP Filter
 - Wireless security:
 - WEP 64 / 128 bit
 - WPA-PSK (TKIP/AES)
 - WPA2-PSK (TKIP/AES)
 - LED control: On / Off
- Browser support:
 - IE 6.0 or above
 - Firefox (limitations)
 - Safari (limitations)

• Software Features:

- Operating system support (software) :
 - Windows 2000, XP and Vista
- View channel: 16 CHs / Cameras
 - Record
 - Playback
 - Motion detection
 - IPFinder: auto search IP address of camera in LAN

• Safety :

- CE, FCC, WEEE, RoHS

• Retail package contains :

- IPC2OUT
- Antenna
- Ethernet cable
- 2 x Power adapter
- Wall & Roof mounting kit
- Application software CD
- Installation guides

• Ean / Order code :

- 64 18949 023082

A-LINK is a registered trademark of A-LINK.

<http://www.a-link.com>

All rights reserved

IPC2out specs UK 04.08.06

